

SPECIFICATIONS FOR WALL TEXTILES WITH FIBERGLASS CORE

SPECIFICATIONS

STYLE	lkat:	Bamboo(FG):	Chain Weave:
WIDTH	72" wide (1.83 meters)	72" wide (1.83 meters)	72" wide (1.83 meters)
THICKNESS	0.055" (0.140 cm)	0.055" (0.140 cm)	0.055" (0.140 cm)
WEIGHT	20 oz / sq yd (0.68 kgs/m2)	20 oz / sq yd (0.68 kgs/m2)	25 oz / sq yd (0.85 kgs/m2)

STYLE	Basketweave (FG):	Frost:	Rib Weave(FG):
WIDTH	72" wide (1.83 meters)	72" wide (1.83 meters)	72" wide (1.83 meters)
THICKNESS	0.055" (0.140 cm)	0.055" (0.140 cm)	0.08" (0.203cm)
WEIGHT	27oz/sq yd (0.92 kg/m2)	25oz/sq yd (0.85 kg/m2)	34oz/sq yd (1.15 kg/m2)

STYLE	Boucle:	Lounge:	Kono:
WIDTH	72" wide (1.83 meters)	72" wide (1.83 meters)	72" wide (1.83 meters)
THICKNESS	0.055" (0.140 cm)	0.055" (0.140 cm)	0.08" (0.203cm)
WEIGHT	20oz/sq yd (0.68 kg/m2)	20oz/sq yd (0.68 kg/m2)	35oz/sq yd (0.85 kg/m2)

Fiber content of all styles
Face: 85% vinyl, 15% fiberglass. Backing: 100% polyester, non-woven scrim backing.

TESTS CONDUCTED + RESULTS

Colorfastness	Complies Cat VI Type III
Washability	Complies Cat VI Type II
Scrubbability	Complies Cat VI Type III
Abrasion	Complies Cat III
Breaking Strength	Complies Cat VI Type III
Crocking	Complies Cat VI Type III
Stain Resistance	Complies Cat VI Type III
Tear test Complies	Cat VI Type III
Blocking Resistance	Complies Cat VI Type III
Coating Complies	Cat VI Type III
Cold Cracking	Complies Cat III
Heat Aging	Complies Cat VI Type III
Flame Spread *	Class A *
Smoke developed	Class A
Shrinkage Complies	Cat VI Type III

Please note: Individual test results are maintained at the manufacturing facility and are available if required. All tests listed above were performed by a certified independent laboratory.

*With sprinklers