
MAINTENANCE INSTRUCTIONS FOR PLYNYL® WALL COVERING

1. General Maintenance Instructions:

1.1 Routine maintenance and diligent attention to stain causing spills will provide a long useful life and help maintain the original beauty of Plynyl. Frequency depends on the amount of soil and dirt Plynyl is exposed to. Dirt and soil will degrade any wall covering so proper maintenance will increase its natural life cycle.

1.2 Prompt attention to stains will eliminate any possible reaction between the staining agent and the wall covering. Time is crucial when removing materials containing colors and/or solvents. Permanent discoloration may transpire if soilants remain on the wall covering for an extended period of time.

1.3 Dirt and smudges can be removed with mild soap (use the lowest Ph detergent that proves to be successful) and warm water. Cleaning from the bottom, upward is most effective. Rinse thoroughly with clean water from the top down, using a sponge.

1.4 Dry wall covering with a soft cloth or towel. Make sure it is lint-free.

1.5 Do not use Acetone, Pine-Sol or Citrus based cleaners as they can damage Plynyl.

1.6 A small area should be tested with all cleaners prior to use to insure compatibility.

NOTE: Stains that cannot be removed under the listed procedures can be treated with a 1:10 bleach to water solution. Mist the solution on the area of discoloration and allow to dwell for 5 minutes. Rinse the area with water only in order to remove the bleach residue. Allow to dry completely. Some stains may require a professional to complete the stain removal process. This warranty covers Plynyl Fabric when properly handled and installed for normal use as wall covering or furniture fabric. The exclusive limited warranty is for the purchaser only and is non-transferable. *Standards and minimum specifications are on file in the Chilewich colorfastness and wear policy.